



# Rocky Mountain Siding Collection

## Teton Canyon – SA003



### Available Specifications

- Species: Alaskan Pine\*, White Pine, Cedar\*, Redwood\*, Ipe\*
  - Finish - Prefinish Available - Sikken's Wood Finish Specialist
  - Colors - Log & Siding, SRD, Semi-Transparent, Rubbol Solid, Custom colors also available
  - Edge detail - Double Step Tongue & Groove - Hidden Fasteners
  - Surface - Adze Face and Softened Live Edges
  - Thickness - 2" Nominal
  - Widths - 6", 8", 10", & 12" Nominal ([Click for pattern details](#))
  - Grades (specie dependent) - Tight Knot, , Select, Clear Vertical Grain
- \* Non-resinous - no pitch bleed



### Installation Guide

Recommended  $1\frac{1}{4}$ " penetration of stainless steel siding screw or nail into wood substrate (sheeting and wall studs) behind siding. For horizontal installation, nail into each wall stud. Vertical installation requires additional blocking every 32" between wall studs. Use 3" trim screw or 10d stainless steel nail provided there is no foam board behind siding.

[Click to enlarge](#)

[www.kwaterskibros.com](http://www.kwaterskibros.com)

*Nation's Largest Selection of Creative Wood Products*